

H05V2-K / H07V2-K

Cavi energia / Har cables / Cables har / Energiekabel



Sezione Section Section Nennquerschnitt mm ²	Diam. Esterno Outer Diameter Diamètre extérieur Aussendiameter mm	Peso Rame Copper Weight Poids du Cuivre Kupferzahl Kg/Km	Peso Cavo Cable Weight Poids du Cable Gewicht Kg/Km
1x0,50	2,1	4,8	8
1x0,75	2,3	7,2	12
1x1	2,5	9,6	14
1x1,5	2,9	14,4	20
1x2,5	3,6	24	32
1x4	4,1	38	45
1x6	4,7	58	65
1x10	6,2	96	120
1x16	7,1	154	170
1x25	8,7	240	260
1x35	9,9	336	350

Conduttore multifilo flessibile in rame rosso
Isolamento in PVC colorato 90°C
Temperatura d'esercizio: -20°C/ +90°C
Tensione d'esercizio: 300/500V per H05V2-K
Tensione d'esercizio: 450/750V per H07V2-K

Flexible conductor in red copper
90°C PVC insulation
Operating temperature: -20°C/+90°C
Operating voltage: 300/500v for H05V2-K
Operating voltage: 450/750v for H07V2-K

Conducteur flexible en cuivre rouge
Isolation en PVC special 90°C
Temperature de service: -20°C/ +90°C
Tension de service: 300/ 500v pour H05V2-K
Tension de service: 450/ 750v pour H07V2-K

Flexibel Leiter aus blank Kupfer; mehrdrahtig
Isolation aus PVC 90°C
Temperaturbereich: -20°C/+90°C
Nennspannung: 300/500V für H05V2-K
Nennspannung: 450/750V für H07V2-K