

## H05 V-U / H07 V-U

Cavi energia / Har cables / Cables har / Energiekabel



Sezione Section Section Nennquerschnitt mm <sup>2</sup>	Diam. Esterno Outer Diameter Diamètre extérieur Aussendiameter mm	Peso Rame Copper Weight Poids du Cuivre Kupferzahl Kg/Km	Peso Cavo Cable Weight Poids du Cable Gewicht Kg/Km
1x0,50	2.3	4.8	9
1x0,75	2.5	7.2	12
1x1	2.6	9.6	15
1x1,5	3.1	14.4	21
1x2,5	3.8	24	33
1x4	4.4	38.4	48
1x6	4.9	57.6	66

Conduttore in CU Rosso monofilo solido  
Isolamento in PVC colorato  
Temperatura d'esercizio: -5°C / +70°C  
Tensione d'esercizio: 450 / 750 V

Solid Conductor in Red Copper  
Coloured PVC Insulation  
Operating Temperature: -5°C / +70°C  
Operating voltage: 450 / 750 V

Conducteur rigide en Cuivre nu  
Isolation en PVC coloré  
Température de service: -5°C / +70°C  
Tension de service: 450 / 750 V

Kupferleiter, blank, eindrahtig  
Isolation aus farbigen PVC  
Temperaturbereich: -5°C / +70°C  
Nennspannung: 450 / 750 V

