

H01 N2-D

Cavi energia / Har cables / Cables har / Energiekabel



Sezione Section Section Nennquerschnitt mm ²	Diam. Esterno Outer Diameter Diamètre extérieur Aussendiameter mm	Peso Rame Copper Weight Poids du Cuivre Kupferzahl Kg/Km	Peso Cavo Cable Weight Poids du Cable Gewicht Kg/Km
1x10	8.7	96	150
1x16	9.9	153.6	210
1x25	11.4	240	300
1x35	12.8	336	400
1x50	14.9	480	560
1x70	17.3	672	780
1x95	19.3	912	1010

Conduttore flessibile in CU Rosso
Guaina esterna in Polychloroprene,
qualità EM5
Temperatura d'esercizio: -20°C / +85°C
Tensione d'esercizio: 100 / 100 V

Flexible Conductor in Red CU
Outer Sheath in Polychloroprene, quality EM5
Operating Temperature: -20° C/ +85°C
Operating voltage: 100 / 100 V

Conducteur flexible en Cuivre nu
Manteau extérieur en polychloroprene,
qualité EM5
Température de service: -20° C/ +85°C
Tension de service: 100 / 100 V

Flexibel Leiter aus blank Kupfer
Aussenmantel aus Polychloropren; Type EM5
Temperaturbereich: -20°C/+85°C
Nennspannung: 100 / 100 V