

H03 VV-F

Cavi energia / Har cables / Cables har / Energiekabel



Sezione Section Section Nennquerschnitt mm ²	Diam. Esterno Outer Diameter Diamètre extérieur Aussendiameter mm	Peso Rame Copper Weight Poids du Cuivre Kupferzahl Kg/Km	Peso Cavo Cable Weight Poids du Cable Gewicht Kg/Km
2x0,50	5.9	9.6	34
3G0,50	6.3	14.4	41
4G0,50	6.9	19.2	49
2x0,75	6.3	14.4	42
3G0,75	6.7	21.6	51
4G0,75	7.3	28.8	62

Conduttore multifilo in CU Rosso
Isolamento in PVC
Guaina esterna in PVC nera, bianca, o grigia
Temperatura d'esercizio: +5°C / +60°C
Tensione d'esercizio: 300 / 300 V

Flexible Conductor in Red CU
PVC Insulation
PVC Outer Sheath in black, white or grey
Operating Temperature: +5°C / +60°C
Operating voltage: 300 / 300 V

Conducteur flexible en Cuivre nu
Isolation en PVC
Manteau extérieur en PVC blanc, gris ou noir
Température de service: +5°C / +60°C
Tension de service: 300 / 300

Flexibel Leiter aus blank Kupfer; mehrdrahtig
Isolation aus PVC
Aussenmantel aus schwarzen, weissen oder grauen PVC
Temperaturbereich: +5°C/+60°C
Nennspannung: 300/500 V

