

H05 VV-F

Cavi energia / Har cables / Cables har / Energiekabel



Sezione Section Section Nennquerschnitt mm ²	Diam. Esterno Outer Diameter Diamètre extérieur Aussendiameter mm	Peso Rame Copper Weight Poids du Cuivre Kupferzahl Kg/Km	Peso Cavo Cable Weight Poids du Cable Gewicht Kg/Km
2x0,75	7.2	14.4	53
3G0,75	7.6	21.6	63
4G0,75	8.3	28.8	76
5G0,75	9.3	36	96
2x1	7.5	19.2	61
3G1	8	28.8	73
4G1	9	38.4	91
5G1	9.8	48	110
2x1,5	8.6	28.8	81
3G1,5	9.4	43.2	100
4G1,5	10.5	57.6	127
5G1,5	11.6	72	160
2x2,5	10.6	48	125
3G2,5	11.4	72	157
4G2,5	12.5	96	191
5G2,5	13.9	120	238
2x4	12.1	76.8	173
3G4	13.1	115.2	216
4G4	14.3	153.6	265
5G4	16.1	192	340

Conduttore multifilo in CU Rosso
Isolamento in PVC
Guaina esterna in PVC nera, bianca, o grigia
Temperatura d'esercizio: +5°C / +60°C
Tensione d'esercizio: 300 / 300 V

Flexible Conductor in Red CU
PVC Insulation
PVC Outer Sheath in black, white or grey
Operating Temperature: +5°C / +60°C
Operating voltage: 300 / 300 V

Conducteur flexible en Cuivre nu
Isolation en PVC
Manteau extérieur en PVC blanc, gris ou noir
Température de service: +5°C / +60°C
Tension de service: 300 / 300

Flexibel Leiter aus blank Kupfer; mehrdrahtig
Isolation aus PVC
Aussenmantel aus schwarzen, weissen oder grauen PVC
Temperaturbereich: +5°C/+60°C
Nennspannung: 300/500 V

