

## H07 V-R

Cavi energia / Har cables / Cables har / Energiekabel



Sezione Section Section Nennquerschnitt mm <sup>2</sup>	Diam. Esterno Outer Diameter Diamètre extérieur Aussendiameter mm	Peso Rame Copper Weight Poids du Cuivre Kupferzahl Kg/Km	Peso Cavo Cable Weight Poids du Cable Gewicht Kg/Km
1x10	6.4	96	120
1x16	7.4	154	190
1x25	9.1	240	286
1x35	10.3	336	380
1x50	12.4	480	530
1x70	13.6	672	740
1x95	15.8	912	990
1x120	17.4	1152	1260
1x150	19.8	1440	1570
1x185	21.6	1776	1930
1x240	24.6	2304	2490

Conduttore in CU Rosso multifilo solido  
Isolamento in PVC colorato  
Temperatura d'esercizio: -5°C / +70°C  
Tensione d'esercizio: 450 / 750 V

Solid Conductor in Red Copper  
Coloured PVC Insulation  
Operating Temperature: -5°C / +70°C  
Operating voltage: 450 / 750 V

Conducteur rigide en Cuivre nu  
Isolation en PVC coloré  
Température de service: -5°C / +70°C  
Tension de service: 450 / 750 V

Hart Leiter aus blank Kupfer; mehrdrahtig  
Isolation aus farbigen PVC  
Temperaturbereich: -5°C / +70°C  
Nennspannung: 450 / 750 V

