

## H05Z-K / H07Z-K

Cavi energia / Har cables / Cables har / Energiekabel



Sezione Section Section Nennquerschnitt mm <sup>2</sup>	Diam. Esterno Outer Diameter Diamètre extérieur Aussendiameter mm	Peso Rame Copper Weight Poids du Cuivre Kupferzahl Kg/Km	Peso Cavo Cable Weight Poids du Cable Gewicht Kg/Km
1x1,5	3	14.4	19
1x2,5	3.7	24	30
1x4	4.2	38	45
1x6	4.8	58	63
1x10	6.2	96	106
1x16	7.4	154	162
1x25	9.8	240	251
1x35	13.5	336	350
1x50	13.5	480	500
1x70	15.5	672	700
1x95	18	912	950
1x120	20	1152	1200
1x150	23	1440	1500
1x185	25	1776	1820
1x240	27	2304	2450

Conduttore multifilo in CU Rosso  
Isolante elastomerico EI5 (LSZH)  
Temperatura d'esercizio: -5°C / +90°C  
Tensione d'esercizio: 450 / 750 V

Flexible conductor in Red Copper  
Coloured LSZH Insulation  
Operating Temperature: -5°C / +90°C  
Operating voltage: 450 / 750 V

Conducteur flexible en Cuivre nu  
LSZH Isolation coloré  
Température de service: -5°C / +90°C  
Tension de service: 450 / 750 V

Flexibel Leiter aus blank Kupfer  
Halogenfreie Isolation; Type EI5  
Temperaturbereich: -5°C/+90°C  
Nennspannung: 450/750 V



Eca